

FEATURES

- Average Forward Current: $I_{F(AV)}=1A$
- Polarity: Color band denotes cathode



SMA

Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
S2A-S2M	SMA	S2★	5000

★:From A-M



MAXIMUM RATINGS (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Test Conditions	S2						
				A	B	D	G	J	K	M
Repetitive Peak Reverse Voltage	V _{RRM}	V		50	100	200	400	600	800	1000
MaximumRMS Voltage	V _{RMS}	V		35	70	140	280	420	560	700
Average Forward Current	I _{F(AV)}	A	60Hz Half-sine wave, Resistance load, T _L =100℃	2.0						
Surge(Non-repetitive)Forward Current	I _{FSM}	A	60Hz Half-sine wave, 1 cycle, Ta=25℃	50						
Operation Junction and Storage Temperature Range	T _J , T _{STG}	℃		-55 ~ +150						

ELECTRICAL CHARACTERISTICS (Ta=25°C unless otherwise specified)

Item	Symbol	Unit	Test Condition		S2						
					A	B	D	G	J	K	M
Peak Forward Voltage	V _F	V	I _F =2.0A		1.1						
Peak Reverse Current	I _{RRM1}	μA	V _{RM} =V _{RRM}	T _a =25℃	5.0						
	T _a =125℃			125							
Thermal Resistance(Typical)	R _{θJ-A}	℃/W	Between junction and ambient		53						
	R _{θJ-L}		Between junction and terminal		16						

Notes:

Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.27" x 0.27" (7.0 mm x 7.0 mm) copper pad areas

Typical Characteristics

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: MAXIMUM NON-REPETITIVE FORWARD URGE CURRENT




FIG.3: TYPICAL FORWARD CHARACTERISTICS






FIG.4: TYPICAL REVERSE CHARACTERISTICS



SMA Package Outline Dimensions



Dimensions in inches and (millimeters)